VOLUNTARY DISPOSAL

IGLUS

Waste collection banks of classic design







VOLUNTARY DISPOSAL



IGLUS

Waste collection bank for voluntary sorted waste disposal. Low visual impact thanks to its low-key design. Basic characteristic: the useable capacity is the same as its nominal capacity to optimize the use of space. Product certified according to EN 13071-1:2008 standards.

TECHNICAL FEATURES

Body and bottom material:

- 100% recyclable linear polyethylene, mass coloured and UV resistant
- Manufacturing process:
- rotational moulding

Frame:

- polyethylene monocoque body without joints and welds, with differentiated thicknesses, upper side round-shaped to increase resistance
- steel internal handling structure, hooks and hinges
- polyethylene base with two swing doors or cone-shaped reinforced with steel braces
- all steel parts are hot-galvanized according to EN ISO 1461 standards

Insertion apertures, variants:

- two opposite apertures on inclined top
- 200x250 mm splinter-proof rubber rosettes
- hooded aperture with rubber protection
- 210x390 mm aluminium hinged gate with return spring
- 270x360 mm gate for large items, with lock

Opening of bottom, variants:

- two downward swinging doors hinged to the sides of the body and moved by rigid bars with asymmetric closing system for exact coupling of the splinterproof bases
- cone-shaped bottom moved by rigid central bars anchored to the doublehook emptying system

Emptying:

• by means of double-hook standard crane

Markings:

· decals with waste collection graphics and instructions

Standard colours:

- light blue, pastel yellow, pastel green, white, blue, yellow, green
- other colours on request for minimum quantities

ed th		
by er-	Colours	

Model	Bottom	Nominal capacity	Useful capacity	Width	Depth	Height with hook	Height without hook	Empty weight	Admissible weight
MRA20Ex2xx	with two doors	2.000	1.863	1.650 mm	1.200 mm	1.820 mm	1.670 mm	76 kg	872 kg
MRA22Ex3xx	cone bottom	2.200	2.080	1.650 mm	1.650 mm	1.760 mm	1.600 mm	80 kg	964 kg
MRA25Ex2xx	with two doors	2.500	2.450 ı	1.650 mm	1.650 mm	1.830 mm	1.670 mm	85 kg	1.084 kg
MRA26Ex4xx	cone bottom	2.600	2.531	1.900 mm	1.650 mm	1.760 mm	1.600 mm	92 kg	1.138 kg
MRA30Ex4xx	with two doors	3.000	2.975	1.900 mm	1.650 mm	1.830 mm	1.670 mm	122 kg	1.309 kg

